

These circulators should be used in clean and dry commercial applications - such as schools, shops, offices or warehouses.

### Commercial Circulator

Motor, blades, guards, and mount are packed and shipped in a single UPS-able carton.



**MOUNT** 





MOUNT

▲ WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

### **Features**

- · Black semi-gloss powder coated finish
- Pull chain switch
- SIT type 3 conductor, 9' long cord
- Coated steel guards with retaining clips
- Steel hub/spider aluminum paddle blades
- Pole adjusts center of fan from 43" to 60"
- Meets OSHA standards / 1-Year limited warranty
- Imported to TPI specifications

## **Motor Specifications**

• 1-Phase

- 120V
- 1/4 HP, 1/3 HP on HD Models
- 3-Speed

Ball bearing

• Permanently lubricated

Open ventilated

· Permanent split capacitor

## Standard Non-Oscillating Models

MFG CATALOG	MFG MFG CATALOG MODEL NUMBER NUMBER	SIZE	НР	TYPE	MOUNT TYPE	CFM*			VELOCITY PROFILE	AMPS	WT.	LIST
						HIGH	MED	LOW	CFM / Area Sq Ft	(HIGH)	(LBS)	
08778002	CACU 20-P	20"	1/10	Non - Oscillating	Pedestal Mount	1780	1600	1420	3300 / 125	1.4	52	382
08778102	CACU 20-W				Wall Mount						48	344
08706202	CACU 24-P	24"	1/4		Pedestal Mount	3400	3100	2800	5400 / 220	2.3	63	563
08706402	CACU 24-W				Wall Mount						43	481
08697402	CACU 30-P	30"	1/4		Pedestal Mount	4200	3800	3500	6700 / 240	2.4	66	620
08706302	CACU 30-W				Wall Mount	4200					46	497
08761702	CACU 30-P-HD	30"	1/3		Pedestal Mount	5000	4600	4200	7000 / 250	3.60	56	722

<sup>\*</sup>Measured 2 feet from face of fan

Note: Stocked models may differ in appearance from photograph

# TPI Commercial Oscillating Fans

## Standard Oscillating Models



MFG CATALOG NUMBER	MFG MODEL NUMBER	SIZE	НР	TYPE	MOUNT TYPE	CFM*			VELOCITY PROFILE		AMPS		WT.	LIST
						HIGH	MED	LOW	CFM / Area Sq Ft	HIGH	MED	LOW	(LBS)	2.51
08748902	CACU 24-PO	24"	- 1/4	Oscillating	Pedestal Mount	3200	3000	2800	5100 / 230	1.45	1.15	1.1	68	663
08749102	CACU 24-WO	24			Wall Mount								48	568
08749002	CACU 30-PO	30"			Pedestal Mount	4200	3800	3500	6700 / 250	2.0	1.8	1.6	70	697
08749202	CACU 30-WO				Wall Mount								51	617
08761802	CACU 30-PO-HD	30"	1/3		Pedestal Mount	5000	4600	4200	7000 / 250	3.60	3.02	2.94	64	893



#### Notes:

\*Measured 2 feet from face of fan
Stocked models may differ in appearance from photograph - sizes are nominal
Units imported to TPI specifications.

warning: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.