

Model		G25WMI-2A-T4i			G40WMI-2A-T4i			G70WJD-2A-T3			G90WJD-2A-T3			G145WJD-2A-T3			
Prime Power Rating		Amps	kW	kVA	Amps	kW	kVA	Amps	kW	kVA	Amps	kW	kVA	Amps	kW	kVA	
	@ 480V-3Ø, 0.8PF		30	20	25	44	29	36	87	58	73	113	75	94	173	115	144
	@ 240V-3Ø, 0.8PF		60	20	25	87	29	36	174	58	73	226	75	94	346	115	144
	@ 208V-3Ø, 0.8PF		69	20	25	101	29	36	201	58	73	236	68	85	368	106	133
	@ 240V-1Ø, 1.0PF	4 Wire	28	20	20	40	29	29	81	58	58	94	68	68	147	106	106
		Zig-Zag	65	15.6	15.6	89	21	21	188	45	45	221	53	53	346	83	83
@ 120V-1Ø, 1.0PF	4 Wire	56	20	20	81	29	29	161	58	58	189	68	68	294	106	106	
	Zig-Zag	65 × 2	15.6	15.6	89 × 2	21	21	188 × 2	45	45	221 × 2	53	53	346 × 2	83	83	
Engine	Make	Mitsubishi			Mitsubishi			John Deere			John Deere			John Deere			
	Model	S4Q2-Y362IR			S4S-Y262SD			4045TF285E			4045HF285			4045HF485			
	Power Output @ 1800RPM - HP (kWm)	31 (23)			42 (32)			90 (67)			115 (86)			177 (132)			
	Emissions Tier Level	Tier 4i			Tier 2			Tier 3			Tier 3			Tier 3			
	Fuel Tank Capacity - Gal (L)	36 (136)			47 (178)			92 (348)			172 (651)			172 (651)			
	Runtime @ 100% Load - Hr	18.9			18.2			21			22.3			19.8			
Dimensions w/ Running Gear	Length - in (mm)	131 (3327)			144.4 (3668)			155.8 (3957)			165.8 (4211)			165.8 (4211)			
	Width - in (mm)	59.5 (1511)			67 (1702)			68.7 (1745)			71.7(1821)			71.7(1821)			
	Height - in (mm)	67 (1702)			68 (1727)			82.4 (2093)			83.6 (2123)			83.6 (2123)			
	Operating Weight - lb (kg)	2588 (1174)			3508 (1591)			5260 (2386)			6466 (2933)			7220 (3275)			
Sound Level @ 23 ft (7m) and 100% Load - dB(A)	66			66			68			68			71				
Model		G185WJD-2A-T3			G240			G290			G450			G570			
Prime Power Rating		Amps	kW	kVA	Amps	kW	kVA	Amps	kW	kVA	Amps	kW	kVA	Amps	kW	kVA	
	@ 600V-3Ø, 0.8PF	*			230	191	239	279	232	290	448	373	466	539	448	560	
	@ 480V-3Ø, 0.8PF		220	146	183	287	191	239	349	232	290	549	365	456	686	456	570
	@ 240V-3Ø, 0.8PF		439	146	183	574	191	239	698	232	290	1098	365	456	1371	456	570
	@ 208V-3Ø, 0.8PF		500	144	180	607	175	219	805	232	290	1259	363	454	1416	408	510
	@ 240V-1Ø, 1.0PF	4 Wire	200	144	144	243	175	175	322	232	232	504	363	363	567	408	408
		Zig-Zag	458	110	110												
@ 120V-1Ø, 1.0PF	4 Wire	400	144	144	486	175	175	644	232	232	1008	363	363	1133	408	408	
	Zig-Zag	458 × 2	110	110													
Engine	Make	John Deere			John Deere			Cummins			Cummins			Cummins			
	Model	6068HF285			6068HF485			QSL9-G3			QSX15-G9			QSX15-G9			
	Power Output @ 1800RPM - HP (kW)	216 (161)			286 (213)			352 (262)			555 (414)			680 (507)			
	Emissions Tier Level	Tier 3			Tier 3			Tier 3			Tier 2			Tier 2			
	Fuel Tank Capacity - Gal (L)	254 (960)			254 (960)			386 (1461)			574 (2173)			574 (2173)			
	Runtime @ 100% Load - Hr	23.2			18.8			20.9			22.3			18.4			
Dimensions w/ Running Gear	Length - in (mm)	203.9 (5179)			203.9 (5179)			220.9 (5611)			260.9 (6627)			260.9 (6627)			
	Width - in (mm)	75.7 (1923)			75.7 (1923)			77.7 (1974)			85.9 (2182)			85.9 (2182)			
	Height - in (mm)	94.8 (2408)			94.8 (2408)			111.4 (2830)			119.8 (3043)			119.8 (3043)			
	Operating Weight - lb (kg)	9166 (4158)			9678 (4390)			11957 (5424)			18271 (8288)			18573 (8425)			
Sound Level @ 7m (23ft) and 100% Load - dB(A)	68			69			70			74			76				

* Dedicated 600V alternator available for G240-G570 models