



SPECIFICATION DATA SHEET I MODEL: 40TCG





The TRANSCUBE™ 40TCG is a versatile fuel deployment solution for larger diesel-powered equipment. With 1,000 gallons of back-up fuel, your need for fuel truck visits is decreased, which in turn helps you to lower your carbon footprint and your expenses!

- Transportable. Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- Stackable. Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- Accessible. Access manway for maintenance and inspection of inner tank. Removable inner tank. for servicing and cleaning.
- Efficient. Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- Environmentally Safe. Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATIONS

STANDARD FITTINGS: High accuracy contents gauge; 3"Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent. OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.

Capacity (Brim-Fill) Litres: 3790	Bund Material Thickness (in): 1/8"
Capacity (Brim-Fill) Imperial Gallons: 833.68	Inner Tank Material Thickness (in): 1/8"
Capacity (Brim-Fill) US Gallons: 1000	Weight Empty (lbs/kg): 2724 lbs (1235.59kg)
Dimension Length (mm/in): 2311.4 mm/91"	Weight Full (lbs/kg): 9370 lbs (4250.16kg)
Dimension Width (mm/in): 2209.8 mm/87"	Approvals: UL142, ULC S-601-07, NFPA,
Dimension Height (mm/in): 1219.2 mm/48"	Transport Canada, Vlarem, Kiwa
Dimension Cabinet Opening (mm/in): 850.9 mm x 355.6 mm/ 33.5" x 14"	



