



## **SPECIFICATION DATA SHEET I MODEL: 50TCG**





The **TRANS**CUBE™ 50TCG is a versatile fuel deployment solution for larger diesel-powered equipment. With 1,240 gallons of back up fuel, your need for fuel truck visits is decreased, which in turn helps you to lower your carbon footprint and your expenses!

- Transportable. Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
- **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- **Environmentally <u>Safe</u>**. Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

## **SPECIFICATIONS**

STANDARD FITTINGS: High accuracy contents gauge; 3"Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.

OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.

Capacity (Brim-Fill) Litres: 4535	Bund Material Thickness (in): 1/8"
Capacity (Brim-Fill) Imperial Gallons: 998	Inner Tank Material Thickness (in): 1/8"
Capacity (Brim-Fill) US Gallons: 1198	<b>Weight Empty (lbs/kg):</b> 3696 lbs (1676kg)
Dimension Length (mm/in): 2308 mm/90.87"	<b>Weight Full (lbs/kg):</b> 13695 lbs (6211kg)
Dimension Width (mm/in): 2307 mm/90.85"	Approvals: UL142, ULC S-601-07, SUN IBC Type 31A,
Dimension Height (mm/in): 1319 mm/51.93"	UN DOT, NFPA, Transport Canada, Vlarem, Kiwa
Dimension Cabinet Opening (mm/in): 850.9 mm x 355.6 mm/ 33.5" x 14"	



