F COMMERCIAL JOBS WITH THE I-SERIES DEHUS FROM DRI-EAZ



> 130 PINTS/DAY AT AHAM > 200 PINTS/DAY MAX. WATER REMOVAL

> UP TO 400 CFM

> 8 AMPS





170 PINTS/DAY > 240 PINTS/DAY MAX. WATER REMOVAL

- > 22 PINTS/DAY AT 80°F/20% RH
- > UP TO 400 CFM
- > 10.5 AMPS



>> LEADING PERFORMANCE AT ALL HUMIDITY LEVELS.

Self-monitoring system automatically maximizes performance in all conditions.



EASY CLEANING AND MAINTENANCE.

LGR 3500i

Quick access to heat exchange block, coils and pump for cleaning.



SAVE TIME – VIEW INLET AND OUTLET CONDITIONS AT A GLANCE.

Temp and RH displayed in real time on digital control panel.



» PLUS THESE BENEFITS!

- » Remote monitoring compatible. Track conditions on the web using HygroTrac (sold separately)
- » High velocity floor-level output Optional VMax directs warm dry air across floors. Ductable too!





Scan to get detailed specs on our entire dehu line.

> FIND OUT MORE AT DRI-EAZ.COM

15180 JOSH WILSON ROAD | BURLINGTON, WA 98233 | 800-932-3030 | MAY11







