

24CFO-HL

24" Hazardous Location Circulation Fan



Blade Color :	Metallic	Guard Material & Coating :	Powder Coated Steel
Blade Material :	Aluminum	Guard Spacing (inches) :	1/2 OSHA
Blade Pitch (degrees) :	14	Insulation Class :	B
Brand :	Schaefer	Max RPM :	1725
CFM (free air) :	7980	Mount Type Recommended :	WMTA24-B, VS24FMT, VS2430FP
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Nameplate Amps :	9.8/4.9
CFM Range (Free Air) :	5001 - 10000	Number of Wings :	3
CFM/Watt (free Air) :	7.24	Oscillating :	No
Component Certifications :	Motor - CSA	Phase :	1
Cord :	Not included	Power (hp) :	1/2
Country of Origin :	US	Product Color :	Black
Description :	Fan Circulation 24" OSHA, Hazardous Location Motor: Class 1, Division 1, Groups C & D, Class 2, Division 2, Groups E, F, & G	Product Weight (pounds) :	50
Diameter (inches) :	24	Schaefer Performance Test No. :	0762
Distinguishing Feature - Fan :	Hazardous Location Rated	Speed Control Compatible :	No
Drive Type :	Direct	Speeds :	1
Enclosure :	TEFC	Switch :	Not included
Fixed or Portable :	Fixed	Thermal Protection :	Yes
Frequency (Hz) :	60	VFD Compatible :	No
Guard Color :	Black	Voltage :	115/208-230