

# 30", 36", & 42" TPI Industrial Direct Drive Portable Blowers



STANDARD MODEL



SWIVEL MODEL



### Features

- Comes in sizes 30", 36" & 42"
- Rocker switch
- SJT type 3 conductor, 12' long cord
- Aluminum, 3 paddle blade
- Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- 8" wheels
- 36" & 42" swivel model rotates 360° in 12-1/2° increments and locks in place with a steel locking pin
- Meets OSHA standards
- 1 Year limited warranty

### Motor Specifications

- 120V, 1-Phase
- 36"-1/3HP 42"-1/2HP
- Ball bearing
- Permanent split capacitor
- 2-Speed on 36" model
- 1-Speed on 42" model
- Permanently lubricated

### Standard Models

UPC#	MODEL	FAN		MOTOR HP	CFM / RPM		AMPS (HIGH)	SHIPPING WT.(LBS.)	LIST
		SIZE	TYPE		HIGH	LOW			
686334									
874397	PB 30-D	30"	STANDARD	1/4	7800	6000	2.5	65	650
874403	PBS 30-D	30"	SWIVEL					70	775
873048	PB 36-D	36"	STANDARD	1/3	12500 / 1040	9000 / 730	5.5	82	715
873055	PBS 36-D	36"	SWIVEL					110	974
873079	PB 42-D	42"	STANDARD	1/2	15,600 / 1040		6.0	102	1006
873086	PBS 42-D	42"	SWIVEL					128	1235

Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance.

# 48" TPI Industrial Direct Drive Portable Blowers



### Features

- Corrosion and dent proof high density polyethylene housing
- Rocker switch
- SJT type 3 conductor, 12' long cord
- Steel, 2 paddle blade
- Spiral, wire front and rear guards
- 10" wheels
- Swivel model rotates 360° in 12-1/2° increments and locks in place with a steel locking pin
- Meets OSHA standards
- 1 Year limited warranty

### Motor Specifications

- 1-Phase
- 3/4 HP
- Ball bearing
- Permanent split capacitor
- 120V
- 1-Speed
- Permanently lubricated

### Features

UPC#	MODEL	SIZE	FAN TYPE	MOTOR HP	CFM \ RPM	AMPS (HIGH)	DIMENSIONS			SHIPPING WT.(LBS.)	LIST
							"H"	"D"	"W"		
799782	PB 48-D-OP	48"	STANDARD	3/4	17,300 / 824	10.3	58.5	29	55.5	117	1454
799805	PBS 48-D-OP	48"	SWIVEL	3/4	17,300 / 824	10.3	----	----	----	142	1659

Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance.